

SlimPAR 64 RGBA ILS

HIGHLIGHTS

- LED Par designed for any application in need of a compact quad-color wash light
- ILS compatibility for use in the ILS ecosystem
- D-Fi™ USB compatibility for wireless Master/Slave or DMX control
- Generate a broad spectrum of colors and achieve natural-looking color temperatures with punchy amber LEDs
- Convenient access to RGBA color mixing and static colors with or without DMX
- Increase standalone versatility with multiple user-configurable settings
- Save time running cables and extension cords by power linking multiple units
- Fits best in the CHS-30 VIP gear bag



SPECIFICATIONS

- DMX Channels : DMX Channels: 4 or 8
- DMX Connectors : DMX Connectors: 3-pin XLR
- Max Unobstructed Distance : Light Source: 180 LEDs (39 red, 39 green, 51 blue, 51 amber) 0.25 W (20 mA), 50,000 hours life expectancy.
- Light Source : 180 LEDs (39 red, 39 green, 51 blue, 51 amber) 0.25 W (20 mA), 50,000 hours life expectancy.
- Strobe Rate : 0 to 20 Hz
- Beam Angle : 15°
- Field Angle : 24°
- Illuminance : 872 lux @ 2 m
- Power Linking : 33 units @ 120 V; 57 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current : 17 W, 0.2 A @ 120 V, 60 Hz
- Weight : 2.2 lbs. (1 kg)
- Size : 9.7 x 11.1 x 2.5 in (246 x 282 x 64 mm)
- Approvals : CE, RoHS, MET
- Power and Current : 17 W, 0.2 A @ 120 V, 60 Hz
- Power and Current : 17 W, 0.1 A @ 230 V, 50 Hz
- Bracket Mounting Hole : 13 mm
- Optional Controllers : ILS Command

WHAT'S INCLUDED

- SlimPAR 64 RGBA ILS
- Power cord
- Quick Reference Guide